

Package ‘LMMsolver’

April 16, 2024

Type Package

Title Linear Mixed Model Solver

Description An efficient and flexible system to solve sparse mixed model equations. Important applications are the use of splines to model spatial or temporal trends as described in Boer (2023). (<[doi:10.1177/1471082X231178591](https://doi.org/10.1177/1471082X231178591)>).

Version 1.0.7

Date 2024-04-16

License GPL

Encoding UTF-8

LazyData true

Depends R (>= 3.6)

Imports agridat, ggplot2, maps, Matrix, methods, Rcpp (>= 0.10.4), sf, spam, splines

LinkingTo Rcpp

RoxygenNote 7.3.1

Suggests rmarkdown, knitr, tinytest

VignetteBuilder knitr

URL <https://biometris.github.io/LMMsolver/index.html>,
<https://github.com/Biometris/LMMsolver/>

BugReports <https://github.com/Biometris/LMMsolver/issues>

NeedsCompilation yes

Author Martin Boer [aut] (<<https://orcid.org/0000-0002-1879-4588>>),
Bart-Jan van Rossum [aut, cre]
(<<https://orcid.org/0000-0002-8673-2514>>)

Maintainer Bart-Jan van Rossum <bart-jan.vanrossum@wur.nl>

Repository CRAN

Date/Publication 2024-04-16 14:20:02 UTC

R topics documented:

APSIMdat	2
coef.LMMsolve	3
deviance.LMMsolve	4
diagnosticsMME	5
displayMME	5
fitted.LMMsolve	6
LMMsolve	7
LMMsolveObject	9
logLik.LMMsolve	10
multipop	11
obtainSmoothTrend	12
residuals.LMMsolve	13
spl1D	14
summary.LMMsolve	16
Index	18

APSIMdat

Simulated Biomass as function of time using APSIM wheat.

Description

Simulated Biomass as function of time using APSIM wheat.

Usage

APSIMdat

Format

A data.frame with 121 rows and 4 columns.

env Environment, Emerald in 1993

geno Simulated genotype g001

das Days after sowing

biomass Simulated biomass using APSIM; medium measurement error added

References

Bustos-Korts et al. (2019) Combining Crop Growth Modeling and Statistical Genetic Modeling to Evaluate Phenotyping Strategies [doi:10.3389/FPLS.2019.01491](https://doi.org/10.3389/FPLS.2019.01491)

coef.LMMsolve	<i>Coefficients from the mixed model equations of an LMMsolve object.</i>
---------------	---

Description

Obtain the coefficients from the mixed model equations of an LMMsolve object.

Usage

```
## S3 method for class 'LMMsolve'  
coef(object, se = FALSE, ...)
```

Arguments

object	an object of class LMMsolve
se	calculate standard errors, default FALSE.
...	some methods for this generic require additional arguments. None are used in this method.

Value

A list of vectors, containing the estimated effects for each fixed effect and the predictions for each random effect in the defined linear mixed model.

Examples

```
## Fit model on john.alpha data from agridat package.  
data(john.alpha, package = "agridat")  
  
## Fit simple model with only fixed effects.  
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,  
                 data = john.alpha)  
  
## Obtain coefficients.  
coefs1 <- coef(LMM1)  
  
## Obtain coefficients with standard errors.  
coefs2 <- coef(LMM1, se = TRUE)
```

deviance.LMMsolve *Deviance of an LMMsolve object*

Description

Obtain the deviance of a model fitted using LMMsolve.

Usage

```
## S3 method for class 'LMMsolve'  
deviance(object, includeConstant = TRUE, ...)
```

Arguments

object	an object of class LMMsolve
includeConstant	Should the constant in the restricted log-likelihood be included. Default is TRUE, as for example in lme4 and SAS. In asreml the constant is omitted.
...	some methods for this generic require additional arguments. None are used in this method.

Value

The deviance of the fitted model.

Examples

```
## Fit model on john.alpha data from agridat package.  
data(john.alpha, package = "agridat")  
  
## Fit simple model with only fixed effects.  
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,  
                 data = john.alpha)  
  
## Obtain deviance.  
logLik(LMM1)  
  
## Obtain deviance. without constant.  
logLik(LMM1, includeConstant = FALSE)
```

diagnosticsMME	<i>Give diagnostics for mixed model coefficient matrix C and the cholesky decomposition</i>
----------------	---

Description

Give diagnostics for mixed model coefficient matrix C and the cholesky decomposition

Usage

```
diagnosticsMME(object)
```

Arguments

object an object of class LMMsolve.

Value

A summary of the mixed model coefficient matrix and its choleski decomposition.

Examples

```
## Fit model on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit simple model with only fixed effects.
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,
                 data = john.alpha)

## Obtain deviance.
diagnosticsMME(LMM1)
```

displayMME	<i>Display the sparseness of the mixed model coefficient matrix</i>
------------	---

Description

Display the sparseness of the mixed model coefficient matrix

Usage

```
displayMME(object, cholesky = FALSE)
```

Arguments

object an object of class LMMsolve.
cholesky Should the cholesky decomposition of the coefficient matrix be plotted?

Value

A plot of the sparseness of the mixed model coefficient matrix.

Examples

```
## Fit model on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit simple model with only fixed effects.
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,
                 data = john.alpha)

## Obtain deviance.
displayMME(LMM1)
```

fitted.LMMsolve	<i>Fitted values of an LMMsolve object.</i>
-----------------	---

Description

Obtain the fitted values from a mixed model fitted using LMMsolve.

Usage

```
## S3 method for class 'LMMsolve'
fitted(object, ...)
```

Arguments

object	an object of class LMMsolve
...	some methods for this generic require additional arguments. None are used in this method.

Value

A vector of fitted values.

Examples

```
## Fit model on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit simple model with only fixed effects.
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,
                 data = john.alpha)

## Obtain fitted values.
fitted1 <- fitted(LMM1)
```

Description

Solve Linear Mixed Models using REML.

Usage

```
LMMsolve(
  fixed,
  random = NULL,
  spline = NULL,
  group = NULL,
  ginverse = NULL,
  weights = NULL,
  data,
  residual = NULL,
  family = gaussian(),
  offset = 0,
  tolerance = 1e-06,
  trace = FALSE,
  maxit = 250,
  theta = NULL,
  grpTheta = NULL
)
```

Arguments

<code>fixed</code>	A formula for the fixed part of the model. Should be of the form "response ~ pred"
<code>random</code>	A formula for the random part of the model. Should be of the form "~ pred".
<code>spline</code>	A formula for the spline part of the model. Should be of the form "~ spl1D()", "~ spl2D()" or "~spl3D()".
<code>group</code>	A named list where each component is a numeric vector specifying contiguous fields in data that are to be considered as a single term.
<code>ginverse</code>	A named list with each component a symmetric matrix, the precision matrix of a corresponding random term in the model. The row and column order of the precision matrices should match the order of the levels of the corresponding factor in the data.
<code>weights</code>	A character string identifying the column of data to use as relative weights in the fit. Default value NULL, weights are all equal to one.
<code>data</code>	A data.frame containing the modeling data.
<code>residual</code>	A formula for the residual part of the model. Should be of the form "~ pred".
<code>family</code>	An object of class family specifying the distribution and link function.

offset	An optional numerical vector containing an a priori known component to be included in the linear predictor during fitting.
tolerance	A numerical value. The convergence tolerance for the modified Henderson algorithm to estimate the variance components.
trace	Should the progress of the algorithm be printed? Default trace = FALSE.
maxit	A numerical value. The maximum number of iterations for the algorithm. Default maxit = 250.
theta	initial values for penalty or precision parameters. Default NULL, all precision parameters set equal to 1.
grpTheta	a vector to give components the same penalty. Default NULL, all components have a separate penalty.

Details

A Linear Mixed Model (LMM) has the form

$$y = X\beta + Zu + e, u \sim N(0, G), e \sim N(0, R)$$

where y is a vector of observations, β is a vector with the fixed effects, u is a vector with the random effects, and e a vector of random residuals. X and Z are design matrices.

LMMsolve can fit models where the matrices G^{-1} and R^{-1} are a linear combination of precision matrices $Q_{G,i}$ and $Q_{R,i}$:

$$G^{-1} = \sum_i \psi_i Q_{G,i}, R^{-1} = \sum_i \phi_i Q_{R,i}$$

where the precision parameters ψ_i and ϕ_i are estimated using REML. For most standard mixed models $1/\psi_i$ are the variance components and $1/\phi_i$ the residual variances. We use a formulation in terms of precision parameters to allow for non-standard mixed models using tensor product splines.

Value

An object of class LMMsolve representing the fitted model. See [LMMsolveObject](#) for a full description of the components in this object.

See Also

[LMMsolveObject](#), [spl1D](#), [spl2D](#), [spl3D](#)

Examples

```
## Fit models on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit simple model with only fixed effects.
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,
                 data = john.alpha)

## Fit the same model with genotype as random effect.
```



```

LMM1_rand <- LMMsolve(fixed = yield ~ rep,
                     random = ~gen,
                     data = john.alpha)

## Fit the model with a 1-dimensional spline at the plot level.
LMM1_spline <- LMMsolve(fixed = yield ~ rep + gen,
                       spline = ~spl1D(x = plot, nseg = 20),
                       data = john.alpha)

## Fit models on multipop data included in the package.
data(multipop)

## The residual variances for the two populations can be different.
## Allow for heterogeneous residual variances using the residual argument.
LMM2 <- LMMsolve(fixed = pheno ~ cross,
                 residual = ~cross,
                 data = multipop)

## QTL-probabilities are defined by the columns pA, pB, pC.
## They can be included in the random part of the model by specifying the
## group argument and using grp() in the random part.

# Define groups by specifying columns in data corresponding to groups in a list.
# Name used in grp() should match names specified in list.
lGrp <- list(QTL = 3:5)
LMM2_group <- LMMsolve(fixed = pheno ~ cross,
                      group = lGrp,
                      random = ~grp(QTL),
                      residual = ~cross,
                      data = multipop)

```

LMMsolveObject

Fitted LMMsolve Object

Description

An object of class `LMMsolve` returned by the `LMMsolve` function, representing a fitted linear mixed model. Objects of this class have methods for the generic functions `coef`, `fitted`, `residuals`, `loglik` and `deviance`.

Value

An object of class `LMMsolve` contains the following components:

<code>logL</code>	The restricted log-likelihood at convergence
<code>sigma2e</code>	The residual error
<code>tau2e</code>	The estimated variance components
<code>EDdf</code>	The effective dimensions

varPar	The number of variance parameters for each variance component
VarDf	The table with variance components
theta	The precision parameters
coefMME	A vector with all the estimated effects from mixed model equations
ndxCoefficients	The indices of the coefficients with the names
yhat	The fitted values
residuals	The residuals
nIter	The number of iterations for the mixed model to converge
y	Response variable
X	The design matrix for the fixed part of the mixed model
Z	The design matrix for the random part of the mixed model
lGinv	List with precision matrices for the random terms
lRinv	List with precision matrices for the residual
C	The mixed model coefficient matrix after last iteration
cholC	The cholesky decomposition of coefficient matrix C
constantREML	The REML constant
dim	The dimensions for each of the fixed and random terms in the mixed model
term.labels.f	The names of the fixed terms in the mixed model
term.labels.r	The names of the random terms in the mixed model
splRes	An object with definition of spline argument
family	An object of class family specifying the distribution and link function
trace	A data.frame with the convergence sequence for the log likelihood and effective dimensions
.	

logLik.LMMsolve

Log-likelihood of an LMMsolve object

Description

Obtain the Restricted Maximum Log-Likelihood of a model fitted using LMMsolve.

Usage

```
## S3 method for class 'LMMsolve'
logLik(object, includeConstant = TRUE, ...)
```

Arguments

object an object of class LMMsolve

includeConstant Should the constant in the restricted log-likelihood be included. Default is TRUE, as for example in lme4 and SAS. In asreml the constant is omitted.

... some methods for this generic require additional arguments. None are used in this method.

Value

The restricted maximum log-likelihood of the fitted model.

Examples

```
## Fit model on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit simple model with only fixed effects.
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,
                 data = john.alpha)

## Obtain log-likelihood.
logLik(LMM1)

## Obtain log-likelihood without constant.
logLik(LMM1, includeConstant = FALSE)
```

multipop

Simulated QTL mapping data set

Description

Simulated QTL mapping data set

Usage

```
multipop
```

Format

A data.frame with 180 rows and 6 columns.

cross Cross ID, two populations, AxB and AxC

ind Genotype ID

pA Probability that individual has alleles from parent A

pB Probability that individual has alleles from parent B

pC Probability that individual has alleles from parent C

pheno Simulated phenotypic value

obtainSmoothTrend *Obtain Smooth Trend.*

Description

Obtain the smooth trend for models fitted with a spline component.

Usage

```
obtainSmoothTrend(
  object,
  grid = NULL,
  newdata = NULL,
  deriv = 0,
  includeIntercept = FALSE,
  which = 1
)
```

Arguments

object	An object of class LMMsolve.
grid	A numeric vector having the length of the dimension of the fitted spline component. This represents the number of grid points at which a surface will be computed.
newdata	A data.frame containing new points for which the smooth trend should be computed. Column names should include the names used when fitting the spline model.
deriv	Derivative of B-splines, default 0. At the moment only implemented for spl1D.
includeIntercept	Should the value of the intercept be included in the computed smooth trend? Ignored if deriv > 0.
which	An integer, for if there are multiple splxD terms in the model. Default value is 1.

Value

A data.frame with predictions for the smooth trend on the specified grid. The standard errors are saved if 'deriv' has default value 0.

Examples

```
## Fit model on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit a model with a 1-dimensional spline at the plot level.
LMM1_spline <- LMMSolve(fixed = yield ~ rep + gen,
  spline = ~spl1D(x = plot, nseg = 20),
  data = john.alpha)

## Obtain the smooth trend for the fitted model on a dense grid.
smooth1 <- obtainSmoothTrend(LMM1_spline,
  grid = 100)

## Obtain the smooth trend on a new data set - plots 10 to 40.
newdat <- data.frame(plot = 10:40)
smooth2 <- obtainSmoothTrend(LMM1_spline,
  newdata = newdat)

## The first derivative of the smooth trend can be obtained by setting deriv = 1.
smooth3 <- obtainSmoothTrend(LMM1_spline,
  grid = 100,
  deriv = 1)

## For examples of higher order splines see the vignette.
```

residuals.LMMSolve *Residuals of an LMMSolve object.*

Description

Obtain the residuals from a mixed model fitted using LMMSolve.

Usage

```
## S3 method for class 'LMMSolve'
residuals(object, ...)
```

Arguments

object	an object of class LMMSolve
...	some methods for this generic require additional arguments. None are used in this method.

Value

A vector of residuals.

Examples

```
## Fit model on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit simple model with only fixed effects.
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,
                 data = john.alpha)

## Obtain fitted values.
residuals1 <- residuals(LMM1)
```

spl1D

Fit P-splines

Description

Fit multi dimensional P-splines using sparse implementation.

Usage

```
spl1D(
  x,
  nseg,
  pord = 2,
  degree = 3,
  scaleX = TRUE,
  xlim = range(x),
  cond = NULL,
  level = NULL
)

spl2D(
  x1,
  x2,
  nseg,
  pord = 2,
  degree = 3,
  scaleX = TRUE,
  x1lim = range(x1),
  x2lim = range(x2),
  cond = NULL,
  level = NULL
)

spl3D(
  x1,
```

```

x2,
x3,
nseg,
pord = 2,
degree = 3,
scaleX = TRUE,
x1lim = range(x1),
x2lim = range(x2),
x3lim = range(x3)
)

```

Arguments

<code>x, x1, x2, x3</code>	The variables in the data containing the values of the x covariates.
<code>nseg</code>	The number of segments
<code>pord</code>	The order of penalty, default <code>pord = 2</code>
<code>degree</code>	The degree of B-spline basis, default <code>degree = 3</code>
<code>scaleX</code>	Should the fixed effects be scaled.
<code>xlim, x1lim, x2lim, x3lim</code>	A numerical vector of length 2 containing the domain of the corresponding x covariate where the knots should be placed. Default set to NULL, when the covariate range will be used.
<code>cond</code>	Conditional factor: splines are defined conditional on the level. Default NULL.
<code>level</code>	The level of the conditional factor. Default NULL.

Value

A list with the following elements:

- `X` - design matrix for fixed effect. The intercept is not included.
- `Z` - design matrix for random effect.
- `lGinv` - a list of precision matrices
- `knots` - a list of vectors with knot positions
- `dim.f` - the dimensions of the fixed effect.
- `dim.r` - the dimensions of the random effect.
- `term.labels.f` - the labels for the fixed effect terms.
- `term.labels.r` - the labels for the random effect terms.
- `x` - a list of vectors for the spline variables.
- `pord` - the order of the penalty.
- `degree` - the degree of the B-spline basis.
- `scaleX` - logical indicating if the fixed effects are scaled.
- `EDnom` - the nominal effective dimensions.

Functions

- spl2D(): 2-dimensional splines
- spl3D(): 3-dimensional splines

See Also

[LMMsolve](#)

Examples

```
## Fit model on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit a model with a 1-dimensional spline at the plot level.
LMM1_spline <- LMMsolve(fixed = yield ~ rep + gen,
                       spline = ~spl1D(x = plot, nseg = 20),
                       data = john.alpha)

summary(LMM1_spline)

## Fit model on US precipitation data from spam package.
data(USprecip, package = "spam")

## Only use observed data
USprecip <- as.data.frame(USprecip)
USprecip <- USprecip[USprecip$infill == 1, ]

## Fit a model with a 2-dimensional P-spline.
LMM2_spline <- LMMsolve(fixed = anomaly ~ 1,
                       spline = ~spl2D(x1 = lon, x2 = lat, nseg = c(41, 41)),
                       data = USprecip)

summary(LMM2_spline)
```

summary.LMMsolve

Summarize Linear Mixed Model fits

Description

Summary method for class "LMMsolve". Creates either a table of effective dimensions (which = "dimensions") or a table of variances (which = "variances").

Usage

```
## S3 method for class 'LMMsolve'
summary(object, which = c("dimensions", "variances"), ...)

## S3 method for class 'summary.LMMsolve'
print(x, ...)
```


Arguments

object	An object of class LMMsolve
which	A character string indicating which summary table should be created.
...	Some methods for this generic require additional arguments. None are used in this method.
x	An object of class summary.LMMsolve, the result of a call to summary.LMM

Value

A data.frame with either effective dimensions or variances depending on which.

Methods (by generic)

- print(summary.LMMsolve): print summary

Examples

```
## Fit model on john.alpha data from agridat package.
data(john.alpha, package = "agridat")

## Fit simple model with only fixed effects.
LMM1 <- LMMsolve(fixed = yield ~ rep + gen,
                 data = john.alpha)

## Obtain table of effective dimensions.
summ1 <- summary(LMM1)
print(summ1)

## Obtain table of variances.
summ2 <- summary(LMM1,
                 which = "variances")
print(summ2)
```

Index

* datasets

APSIMdat, [2](#)
multipop, [11](#)

APSIMdat, [2](#)

coef.LMMsolve, [3](#)

deviance.LMMsolve, [4](#)

diagnosticsMME, [5](#)

displayMME, [5](#)

fitted.LMMsolve, [6](#)

LMMsolve, [7](#), [16](#)

LMMsolveObject, [8](#), [9](#)

logLik.LMMsolve, [10](#)

multipop, [11](#)

obtainSmoothTrend, [12](#)

print.summary.LMMsolve
(summary.LMMsolve), [16](#)

residuals.LMMsolve, [13](#)

sp11D, [8](#), [14](#)

sp12D, [8](#)

sp12D (sp11D), [14](#)

sp13D, [8](#)

sp13D (sp11D), [14](#)

summary.LMMsolve, [16](#)